

1. (CANCELED)

2. (CURRENTLY AMENDED) ~~The securing system according to claim 1,~~
~~wherein~~ A cargo securing system comprising:

an elongate base member having a front surface and a rear surface along
with a plurality of attachment holes to facilitate attachment of the base member to a
desired surface; and an elongate slot and an elongate recess being formed in the base
member such that the slot communicates with the recess;

at least one adjustable member having an enlarged head and a leg
extending from the head, the head being sized to slide along the recess of the base
member with the leg projecting through and being freely slidable along the slot to
facilitate movement of the adjustable member relative to the base member; and

a rearwardly facing surface of the recess carrying a first interlocking
structure having a repeating pattern and the adjustable member carrying a mating
second interlocking structure having a repeating pattern for mating with the repeating
pattern of the first interlocking structure, and when the first interlocking structure
engages with the second interlocking mating structure, the adjustable member is
retained at a desired position relative to the base member; and

the slot extends through the base member from the front surface
to the rear surface thereof and extends longitudinally along a length of the base
member from adjacent a first end wall to a location adjacent an opposite second end
wall.

3. (CURRENTLY AMENDED) ~~The securing system according to claim 1,~~
~~wherein~~ A cargo securing system comprising:

an elongate base member having a front surface and a rear surface along
with a plurality of attachment holes to facilitate attachment of the base member to a
desired surface; and an elongate slot and an elongate recess being formed in the base
member such that the slot communicates with the recess;

at least one adjustable member having an enlarged head and a leg
extending from the head, the head being sized to slide along the recess of the base
member with the leg projecting through and being freely slidable along the slot to
facilitate movement of the adjustable member relative to the base member; and

a rearwardly facing surface of the recess carrying a first interlocking
structure having a repeating pattern and the adjustable member carrying a mating

second interlocking structure having a repeating pattern for mating with the repeating pattern of the first interlocking structure, and when the first interlocking structure engages with the second interlocking mating structure, the adjustable member is retained at a desired position relative to the base member; and

the slot has an access opening therein which is dimensioned larger than the slot to facilitate passage of the adjustable member therethrough.

4. (CURRENTLY AMENDED) The securing system according to claim [[1]]2, wherein the slot extends parallel to and overlies the recess, and the recess has a width which is wider than a width of the slot.

5. (CURRENTLY AMENDED) The securing system according to claim 3, wherein the head is substantially rectangular in shape and the adjustable member has a generally T-shaped transverse cross-section, the head ~~which~~ is smaller in size than the access opening provided in the base member to facilitate unobstructed passage of the head through the access opening and into the recess.

6. (CURRENTLY AMENDED) The securing system according to claim [[1]]2, wherein the leg extends substantially perpendicular to the head and has a width dimension ~~which is~~ smaller than a width dimension of the slot to facilitate free and unobstructed ~~sliding~~ movement of the leg with respect to the slot.

7. (CURRENTLY AMENDED) The securing system according to claim [[1]]2, wherein a forward facing surface of the ~~adjustment~~ adjustable member, located on two opposed sides of the leg, carries the second interlocking structure which is located to engage with the first interlocking structure of the base member and restrain further movement of the ~~adjustment~~ adjustable member relative to the base member.

Audience

8. (CURRENTLY AMENDED) The securing system according to claim [[1]]2, wherein a thickness of the head, including the second interlocking structure, is less than a depth dimension of the recess to provide adequate clearance of the head within the recess and facilitate ~~sliding~~ adjustable movement of the adjustable member relative to the base member.

9. (WITHDRAWN) The securing system according to claim 8, wherein a rear surface of the enlarged head has a spring mechanism to facilitate biasing of the second interlocking structure of the adjustable member into engagement with the first interlocking structure of the base member.

10. (PREVIOUSLY PRESENTED) The securing system according to claim 6, wherein at least one eyelet is provided adjacent a remote end of the leg, and the at least one eyelet facilitates attachment of a desired strap member to the adjustable member.

11. (WITHDRAWN) The securing system according to claim 6, wherein a hook is provided adjacent a remote end of the leg.

12. (WITHDRAWN-CURRENTLY AMENDED) The securing system according to claim [[1]]2, wherein the repeating pattern of the rearwardly facing surface of the recess carries a repeating is a notched pattern and the repeating pattern of the head of the adjustable member carries a mating repeating is a notched pattern.

13. (CURRENTLY AMENDED) ~~The securing system according to claim 1, wherein~~ A cargo securing system comprising:

an elongate base member having a front surface and a rear surface along with a plurality of attachment holes to facilitate attachment of the base member to a desired surface; and an elongate slot and an elongate recess being formed in the base member such that the slot communicates with the recess;

at least one adjustable member having an enlarged head and a leg extending from the head, the head being sized to slide along the recess of the base member with the leg projecting through and being freely slidable along the slot to facilitate movement of the adjustable member relative to the base member; and

a rearwardly facing surface of the recess carrying a first interlocking structure having a repeating pattern and the adjustable member carrying a mating second interlocking structure having a repeating pattern for mating with the repeating pattern of the first interlocking structure, and when the first interlocking structure engages with the second interlocking mating structure, the adjustable member is retained at a desired position relative to the base member; and

the repeating pattern of the rearwardly facing surface of the recess carries a repeating is a saw tooth pattern and the repeating pattern of the head of the adjustable member carries a mating repeating is a saw tooth pattern.

14. (WITHDRAWN-CURRENTLY AMENDED) The securing system according to claim [[1]]2, wherein the repeating pattern of the rearwardly facing surface of the recess carries a repeating is a wave pattern and the repeating pattern of the head of the adjustable member carries a mating repeating is a wave pattern.

15. (CURRENTLY AMENDED) The securing system according to claim 5, wherein the repeating pattern of the rearwardly facing surface of the recess carries a repeating is a notched pattern and the repeating pattern of the head of the adjustable member carries a mating repeating is a notched pattern. ❖❖❖

16. (WITHDRAWN-CURRENTLY AMENDED) The securing system according to claim [[1]]3, wherein a free end of the adjustable member is coupled to a support strut to form a support bracket for supporting a shelving member. ❖

17. (WITHDRAWN-CURRENTLY AMENDED) The securing system according to claim 16, wherein the support strut comprises a head sized to be received by the access opening and move to and fro along the elongate recess, and the support strut extends from the head at an angle of between about 45 to about 70 degrees. ❖

18. (WITHDRAWN-CURRENTLY AMENDED) The securing system according to claim [[1]]2, wherein a free end of [[the]] a support strut carries a pair of spaced apart surfaces which are located to receive and sandwich a free end of a centralthe leg therebetween. ❖❖

19. (CURRENTLY AMENDED) A kit of parts for a cargo securing system, the kit comprising:

a plurality of fastening members;

a plurality of strap members;

a plurality of elongate base members, with each base member having a front surface and a rear surface with a plurality of attachment holes to facilitate attachment of the base member to a desired surface; and an elongate slot and an elongate recess being formed in the base member such that the elongate slot communicates with the recess;

a plurality of adjustable members with each adjustable member having an enlarged head and a leg extending from the head, the head being sized to slide along the recess of one of the base members with the leg projecting through and being freely slidable along the elongate slot of the base members to facilitate sliding movement of the adjustable member relative to that base member the slot extends through the base member from the front surface to the rear surface thereof and extends longitudinally along a length of the base member from adjacent a first end wall to a location adjacent an opposite second end wall; and ❖❖❖❖

a rearwardly facing surface of each recess carrying a first interlocking structure having a repeating pattern and each of the plurality of adjustable members carrying a mating second interlocking structure having a repeating pattern for mating with the repeating pattern of the first interlocking structure, and when the first interlocking structure of one of the base members engages with the second interlocking mating structure of one of the adjustable members, that adjustable member is retained at a desired position relative to the respective base member.

20. (CURRENTLY AMENDED) A method of securing cargo with a cargo securing system, the method comprising the steps of:

providing an elongate base member with front and rear surfaces and with a plurality of attachment holes to facilitate attachment of the base member to a desired surface; and forming an elongate slot and an elongate recess in the base member such that the slot communicates with recess;

providing at least one adjustable member having an enlarged head and a leg extending from the head, with the head being sized to slide along the recess of the base member with the leg projecting through and being freely slidable along the slot to facilitate sliding movement of the adjustable member relative to the base member the slot extends through the base member from the front surface to the rear surface thereof and extends longitudinally along a length of the base member from adjacent a first end wall to a location adjacent an opposite second end wall; and

carrying a first interlocking structure having a repeating pattern on a rearwardly facing surface of the recess and carrying a mating second interlocking structure having a repeating pattern for mating with the repeating pattern of the first interlocking structure on the adjustable member, and retaining the adjustable member at a desired position relative to the base member when the first interlocking structure engages with the second interlocking mating structure.